

18 June 1964

25X1A

MEMORANDUM FOR: [REDACTED] RFD

THROUGH : Chief, Exploratory Development Laboratory Branch,  
Plans and Development Staff


SUBJECT : Progress Report on "A Standard for Testing Film  
Splices", EDLB project #1008.

1. Activity to date has consisted of the gathering of back-ground information. Copies of numerous published papers and copies of seven different military and federal specifications on splicers have been procured. Also, the Contact Division of the Office of Operations (OO/CD) is contacting the three applicable technical societies (SPSE, SMPTE, and ASTM) for existing and/or pending standards.

2. A preliminary study of equipment at the Photographic Laboratory Branch (PSD/PLB) has been accomplished. The following is a list of their printing and processing equipment for roll film which was examined:

- a. Eastman 9.5" Niagara Printer
- b. Eastman 70 mm Continuous Printer
- c. Log E Continuous Printer
- d. Kodak Versamat Processor
- e. Miller-Holzworth Contact Printer
- f. Log E Contact Printer
- g. Zeiss Portable Processor

3. Of this equipment, the automatic continuous printers are the hardest on film. The LogE SP-10/70 uses the smallest roller, 1:60" dia., and film is wrapped up to approx. 135° maximum around this roller. The take-up and drag forces exerted by the torque motors may well be excessive for 70 mm film on the unit in room 2S707, since this one apparently has no control for adjusting the




SUBJECT: Progress Report on "A Standard for Testing Film Splices",  
EDLB Project #1008

torque when changing from 9 $\frac{1}{2}$ " to 70 mm film. This machine is the roughest on splices. This torque will be measured.

4. The Eastman Niagara Printer reverse bends the film twice, but the rollers are large and very little film breakage occurs. Rollers are 1 15/16" dia., and spacing for reverse bending is 3". A wrap of almost 180° occurs around one of the rollers. This printer subjects film to a jerk when starting and this feature will be examined in detail.

5. At this time a splicer is not being used by PLB. They simply use masking tape for making splices for the contact printers and waterproof plastic tape for the processors.

25X1A



Exploratory Development Laboratory Branch,  
P&DS

25X1A

SENDER WILL CHECK CLASSIFICATION TOP AND BOTTOM			
<input type="checkbox"/> UNCLASSIFIED	<input checked="" type="checkbox"/> CONFIDENTIAL	<input type="checkbox"/> SECRET	
<b>CENTRAL INTELLIGENCE AGENCY OFFICIAL ROUTING SLIP</b>			
TO	NAME AND ADDRESS	DATE	INITIALS
1		18/5	
2		14 Jun 64 R PD	
3		17 Jun 19 64	
4		22 Jun 64	
5		6-19-64	
6		File - Project Folder	
<input type="checkbox"/> ACTION	<input type="checkbox"/> DIRECT REPLY	<input type="checkbox"/> PREPARE REPLY	
<input type="checkbox"/> APPROVAL	<input type="checkbox"/> DISPATCH	<input type="checkbox"/> RECOMMENDATION	
<input type="checkbox"/> COMMENT	<input checked="" type="checkbox"/> FILE	<input type="checkbox"/> RETURN	
<input type="checkbox"/> CONCURRENCE	<input checked="" type="checkbox"/> INFORMATION	<input type="checkbox"/> SIGNATURE	
<b>Remarks:</b> Bill: The results of this investigation may be of value in writing specs for printing and processing equipment. Russ			
FOLD HERE TO RETURN TO SENDER			
FROM: NAME, ADDRESS AND PHONE NO.			DATE
[Redacted] - 40411-73435			18 Jun 64
<input type="checkbox"/> UNCLASSIFIED	<input checked="" type="checkbox"/> CONFIDENTIAL	<input type="checkbox"/> SECRET	

25X1A